

A

Express Mail" mailing label number EL 339 001 053 US.
 of Deposit 6/16/99

Our Case No. 9281/3347
 Client Reference No. JCK US97068

PATENT APPLICATION TRANSMITTAL LETTER

To the Assistant Commissioner for Patents:

Transmitted herewith for filing is the patent application of Takashi Date and Toshiaki Hoshino
 for Liquid Crystal Display Device

Enclosed are:

- ☒ 42 pages of application (including title page), 9 sheet(s) of drawings and the following
 Appendices : None.
- ☐ Preliminary Amendment
- ☒ Declaration and Power of Attorney for Patent Application
- ☒ Assignment transmittal letter and Assignment of the invention to : ALPS ELECTRIC CO., LTD.
- ☒ Submission of Certified Copy of Priority Document and certified copy of Japanese
 Application No. 10-170373.
- ☐ Information Disclosure Statement; PTO-1449 reference A.

Claims as Filed	Col. 1	Col. 2
For	No. Filed	No. Extra
Basic Fee		
Total Claims	6-20	
Indep. Claims	3-3	
Multiple Dependent Claims Present		

*If the difference in col. 1 is less than zero,
 enter "0" in col. 2.

Small Entity	
Rate	Fee
	\$ 380
x\$9=	\$
x\$39=	\$
+\$130=	\$
Total	\$

Other Than Small Entity	
Rate	Fee
	\$ 760
x\$18=	\$
x\$78=	\$
+\$260=	\$
Total	\$760

- ☐ Please charge my Deposit Account No. 23-1925 in the amount of \$: _____. A duplicate copy of this sheet is enclosed.
- ☒ A check in the amount of \$: 760 to cover the filing fee is enclosed.
- ☒ The Assistant Commissioner is hereby authorized to charge payment of the following fees associated with this
 communication or credit any overpayment to Deposit Account No. 23-1925. A duplicate copy of this sheet is enclosed.
 - ☒ Any additional filing fees required under 37 CFR § 1.16.
 - ☒ Any patent application processing fees under 37 CFR §1.17.
- ☐ The Assistant Commissioner is hereby authorized to charge payment of the following fees during the pendency of this
 application or credit any overpayment to Deposit Account No. 23-1925. A duplicate copy of this sheet is enclosed.
 - ☐ Any filing fees under 37 CFR § 1.16 for presentation of extra claims.
 - ☐ Any patent application processing fees under 37 CFR § 1.17.
 - ☐ The issue fee set in 37 CFR § 1.18 at or before mailing of the Notice of Allowance, pursuant to 37 CFR
 § 1.311(b).

Date

6/16/99

Gustavo Siller, Jr.
 BRINKS HOFER GILSON & LIONE
 Registration No. 32,305

Our Case No. 9281/3347
Client Reference No. JCK US97068

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE
APPLICATION FOR UNITED STATES LETTERS PATENT

INVENTORS: Takashi Date
Toshiaki Hoshino

TITLE: LIQUID CRYSTAL DISPLAY
DEVICE

ATTORNEY: Gustavo Siller, Jr.
BRINKS HOFER GILSON & LIONE
P.O. BOX 10395
CHICAGO, ILLINOIS 60610
(312) 321-4200

EXPRESS MAIL NO. EL 339 001 053 US

DATE OF MAILING 6/16/99

LIQUID CRYSTAL DISPLAY DEVICE

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a liquid crystal display device with a metal reflective film and, more particularly, to a structure in which, when a liquid crystal display device is manufactured by sealing a liquid crystal injection hole after a liquid crystal is injected between substrates, an operation of sealing the injection hole can be reliably performed.

2. Description of the Related Art

As shown in FIG. 7 as a conventional configuration of a liquid crystal display device, a liquid crystal display device 3 obtained by sealing a liquid crystal between a pair of substrates 1 and 2 is known. In the exemplified liquid crystal display device 3, a sealing material 4 consisting of a resin and annularly arranged along the peripheral portions of the substrates 1 and 2 is interposed between the substrates 1 and 2, and a liquid crystal is sealed in a space surrounded by the sealing material 4 and the substrates 1 and 2.

Projection portions 5 obtained by partially projecting the sealing material 4 on the center side of one end face of the substrates 1 and 2 (on the center side of the right end

face in FIG. 7) toward the end face side of the substrates 1 and 2 are formed to be spaced apart from each other. These projection portions 5 are caused to reach the end faces of the substrates 1 and 2 to form a liquid crystal injection portion 6. A resin is filled in the liquid crystal injection portion 6 to form a sealed portion 7, and the liquid crystal injection portion 6 is stopped up.

When the liquid crystal display device 3 shown in FIG. 7 is of a reflection type, as shown in FIG. 8, a reflective layer 8 is formed on the rear surface side of the substrate 2.

When operations of injecting a liquid crystal and sealing the liquid crystal are performed to the reflection type liquid crystal display device 3, the operations are performed by, e.g., the procedures described below.

Pairs of substrates 1 and 2, as shown in FIG. 9, obtained in a state in which no liquid crystal is injected and before a sealed portion 7 is formed (i.e., the substrates 1 and 2 in which the injection portion 6 of the sealing material 4 is open) and a vessel 11 in which a liquid crystal 10 is saved are prepared separately from each other.

The pairs of substrates 1 and 2 are made upside down and kept above the vessel 11. This structure as a whole is put in a vacuum atmosphere such as an evacuated furnace.

0934387-06169

The pairs of substrates 1 and 2 are moved downward to dip the peripheral portions of the liquid crystal injection portions 6 of the substrates 1 and 2 into the liquid crystal 10. In this case, since a gap between each pair of substrates 1 and 2 is very small, the liquid crystal 10 can be slightly drawn into the gap between the substrates 1 and 2 from the liquid crystal injection portion 6 by capillary phenomenon.

Upon completion of this operation, when the atmosphere around the vessel 11 and the pairs of substrates 1 and 2 is returned from the vacuum atmosphere to the atmospheric atmosphere, the liquid crystal 10 can be drawn into the entire gap between the substrates 1 and 2 by using a pressure difference between the pressure in the vacuum state between the substrates 1 and 2 and the atmospheric pressure outside the substrates 1 and 2.

Upon completion of the liquid crystal drawing operation into the gaps between the pairs of substrates 1 and 2, operations of stopping up and sealing the liquid crystal injection portions 6 are performed.

The operations are performed as follows. That is, as shown in FIG. 10 of a prior art, the pairs of substrates 1 and 2 subjected to the liquid crystal drawing operation are uprightly arrayed such that the liquid crystal injection portions 6 face the upper side. The distal end of a resin

injection nozzle 12 is sequentially positioned at the openings of the liquid crystal injection portions 6 illuminated with a lighting tool 13, and a resin is injected from the distal end of the resin injection nozzle 12. A resin sticking out of each of the injection portions 6 is wiped off, and the resin of the injection portion 6 is solidified to form the sealed portion 7.

However, since the operation of injecting the resin into the liquid crystal injection portion 6 of each pair of substrates 1 and 2 by using the resin injection nozzle 12 is an important operation which may cause a liquid crystal to leak when erroneous injection such as offsetting of an injection position, the operation must be strictly performed.

However, when the liquid crystal injection portion 6 is illuminated with the lighting tool 13, a problem that the position of the liquid crystal injection portion 6 cannot be easily detected is posed.

This problem is caused by the following reason. That is, when the substrates 1 and 2 are used in a reflection type liquid crystal display device, the reflective films 8 are formed on the entire surfaces of the rear surface sides of the substrates 2. As a result, the liquid crystal injection portion 6 of another pair of substrates 1 and 2 located on the behind side of the substrate 2 in a state in which the pairs of substrates 1 and 2 are arrayed as shown

in FIG. 10 is arranged to shield the liquid crystal injection portion 6 with the reflective layer 8 of the substrate 2 on the front side. For this reason, an operator cannot easily recognize a precise position of the liquid crystal injection portion 6. Position check is to be performed by an image analyzer such as a television camera, all the positions of the liquid crystal injection portions 6 of the pairs of substrates 1 and 2 in an array state cannot be checked from the outside because each reflective layer 8 on the front side shields each liquid crystal injection portion 6 on the rear side. In addition, even if injection positions can be precisely recognized, filling of a resin may not be satisfactorily performed depending on an injection state of the resin. An amount of injection is so excessive that the resin sticking out of the liquid crystal injection portion 6 may be excessively adhered to the peripheral portion of the liquid crystal injection portion 6.

Uneven injection may be caused when a liquid crystal is injected into the pairs of substrates 1 and 2 as shown in FIG. 9. In a vacuum atmosphere, it is difficult to completely recognize and check whether the liquid crystal is filled into the pairs of substrates 1 and 2. For this reason, at present, whether the liquid crystal injection process is completed is recognized by a time parameter of a pressure-reduction time when a vacuum atmosphere is made,

and when a predetermined period of time has elapsed, completion of the injection is determined. However, if defective liquid crystal injection occurs for some reason, substrates 1 and 2 in which the defective liquid crystal injection occurs cannot be detected in the resin sealing process shown in FIG. 10. Therefore, the substrates 1 and 2 in which the defective liquid crystal injection are sealed, and a defective product may be manufactured disadvantageously.

SUMMARY OF THE INVENTION

The present invention has been made in consideration of the above circumstances, and has as its object to provide a liquid crystal display device which, when a liquid crystal injection portion is sealed and stopped up with a resin after a liquid crystal injection operation, makes it possible to easily and precisely perform the operation and makes it possible to easily detect defective liquid crystal injection.

In order to solve the above problems, the present invention provides a liquid crystal display device comprising one substrate on which a metal reflective film is formed, the other substrate arranged opposite to the substrate, a sealing material, interposed between the pair of substrates, for surrounding, together with the substrates,

a liquid crystal injection space formed between the substrates, and a liquid crystal sealed into the liquid crystal injection space, characterized in that a liquid crystal injection portion is formed on the sealing material, a plurality of display electrodes are formed on a substrate surface in a region in which the liquid crystal is sealed, and, on one of the substrates, outside the display electrode forming region, an unformed region of the metal reflective film is formed on a portion including the injection portion of the sealing material.

Since the unformed region of the reflective film is formed on the portion including the injection portion of the sealing material, the position of the injection portion can be easily and reliably checked without being disturbed by the reflective film from the outside of the rear side of the reflective film. Therefore, when operations of uprightly arraying the plurality of substrates 1 and 2, sequentially injecting a resin into a plurality of injection portions, and stopping up the injection portions are performed, the positions of the injection portions can be checked without being disturbed by the reflective films of the other adjacent substrates. Therefore, since the positions of the injection portions can be precisely checked by the region injection portions, an operation of stopping up the injection portions can be reliably performed. In addition,

even if defective injection of a liquid crystal occurs, substrates in which the defective injection occurs can be easily detected. For this reason, a fraction defective can be reduced.

The metal reflective film may employ either one of a structure in which the metal reflective film is additionally formed on one substrate as an independent film and a structure in which the metal reflective film is incorporated in the substrate to be integrated. The sealing material consists of a resin, and is formed on the opposite surface sides of the substrates by a method such as printing. The unformed region of the metal reflective film can be formed at an arbitrary position by the following manner. That is, the metal reflective film is formed by a film forming method after a resist is formed on a substrate, and the resist is peeled from the substrate.

The present invention provides a liquid crystal display device characterized in that, on one substrate, on which a metal reflective film is formed, of a pair of substrates which hold a liquid crystal therebetween, drawn electrodes of the display electrodes are formed at the edges of the substrates outside a region in which a plurality of display electrodes are formed on substrate surfaces in a region which holds the liquid crystal therebetween, and an unformed portion of the metal reflective film is formed in the drawn

When the unformed portion of the metal reflective film is formed in the region in which the drawn electrodes are formed, the drawn electrodes can be easily and reliably formed without being disturbed by the metal reflective film, and the terminals of a drive IC or the like can be easily and reliably connected. In addition, since the positions of terminal connection portions can be checked without being disturbed by the metal reflective film, connection of the terminal connection portions can be easily checked without being shielded by the reflective film.

The present invention further provides a liquid crystal display device comprising one substrate on which a metal reflective film is formed, the other substrate arranged opposite to the substrate, a sealing material, interposed between the pair of substrates, for surrounding, together with the substrates, a liquid crystal injection space formed between the substrates, and a liquid crystal sealed in the liquid crystal injection space, characterized in that a liquid crystal injection portion is formed on the sealing material, a plurality of display electrodes are formed on a substrate surface in a region in which the liquid crystal is sealed, a first drawn electrode for a display electrode for one of the substrates and a second drawn electrode for a display electrode of the other of the substrates are formed

at the edge of one of the substrates, electrode connection means is arranged on the sealing means, the second drawn electrode and the display electrode of the other of the substrates are connected to each other by the electrode connection means, and an unformed portion of the metal reflective film is formed in a region in which the second drawn electrode and the display electrode of the other of the substrates are connected to each other on the sealing material.

In the structure in which the second drawn electrode of one of the substrates is connected to the display electrode of the other of the substrates through the electrode connection means of the sealing material, since no metal reflective film is formed on the connection portion between these electrodes, the drawn electrodes can be easily formed or connected, and the drawn electrode portion can be easily checked without being shielded by the metal reflective film.

The liquid crystal display device may have a configuration characterized in that, on one of the substrates, outside the display electrode forming region, an unformed region of the metal reflective film is formed on a portion including the injection portion of the sealing material.

Since the unformed region of the reflective film is formed on the portion including the injection portion of the

sealing material, the position of the injection portion can be easily checked from the outside. Therefore, when operations of uprightly arraying a large number of substrates, sequentially injecting a resin into a large number of injection portions, and stopping up the injection portions is performed, the positions of the injection portions can be easily seen without being disturbed by the reflective films of the other adjacent substrates. For this reason, the operation of stopping up the injection portion by injection of a resin can be easily and reliably performed.

The liquid crystal display device may have a configuration characterized in that, on one of the substrates, outside the display element forming region, an unformed portion of the metal reflective film is formed in the drawn electrode forming region.

The electrode connection means arranged on the sealing material preferably consists of conductive particles added to the region constituting the sealing material.

If a sealing material has a configuration in which conductive particles are diffused in a resin, when one substrate and the other substrate are brought into airtight contact with each other to sandwich the sealing material, an electrode formed on one substrate and an electrode formed on the other substrate are connected through the conductive particles of the sealing material. Of the conductive

particles of the sealing material, conductive particles sandwiched by the electrodes of a pair of substrates, i.e., conductive particles existing in the direction of the substrate thickness, are sandwiched by the electrodes of the pair of substrates to be in contact with these electrodes, so that these electrodes are electrically connected to each other. However, the conductive particles existing in the direction of the substrate surface are spaced apart from each other. For this reason, electrodes adjacent to each other in the direction of the substrate surface are not short-circuited. Therefore, electrodes adjacent to each other on the same substrate are not short-circuited, and only electrodes which are opposite to each other and must be connected to each other can be reliably connected to each other.

In addition, since a structure having the metal reflective film is incorporated includes the structure in which the conductive particles diffused in the sealing material are sandwiched by the opposing substrates, when the conductive particles are pressed on both the substrates, the conductive particles may break through laminate films formed on portions of the sealing material which are in contact with the substrates. In this case, in a structure in which connection is made on a drawn electrode connection portion by the conductive particles in the sealing material, if a

metal reflective film exists on the connection portion, the conductive particles may reach the metal reflective film to short-circuit the drawn electrode to the metal reflective film. However, such a short circuit can be prevented from being made by forming the unformed region of the metal reflective film on the drawn electrode connection portion.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a side view showing a liquid crystal display device according to the first embodiment of the present invention;

FIG. 2 is a side view showing a liquid crystal display device according to the second embodiment of the present invention;

FIG. 3A is a sectional view of the liquid crystal display device according to the first embodiment of the present invention, and FIG. 3B is a sectional view showing a liquid crystal display device according to the third embodiment of the present invention;

FIG. 4 is a side view showing a liquid crystal display device according to the fourth embodiment of the present invention;

FIG. 5 includes partial enlarged sectional views of the liquid crystal display device according to the embodiment of FIG. 4, in which FIG. 5A is a sectional view showing a

conductive particle diffusion state in which conductive particles do not reach a resin layer, and FIG. 5B is a sectional view showing a conductive particle diffusion state in which conductive particles reach the resin layer;

FIG. 6 includes a plan view and a sectional view showing electrode connection states in the structures shown in FIG. 5, in which FIG. 6A is a plan view showing an electrode connection state in the structure shown in FIG. 5A, and FIG. 6B is a partial enlarged sectional view showing a liquid crystal display device having a structure in which an unformed region of a metal reflective film is not formed;

FIG. 7 is a perspective view showing a structure of a conventional liquid crystal display device;

FIG. 8 is a side view of the liquid crystal display device shown in FIG. 7;

FIG. 9 is a plan view showing a state in which liquid crystal injection is performed in the processes of manufacturing the conventional liquid crystal display device shown in FIG. 8; and

FIG. 10 is a perspective view showing a state in which a resin is injected into a liquid crystal injection hole in the processes of manufacturing the conventional liquid crystal display device shown in FIGS. 7 and 8.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Embodiments of the present invention will be described below in detail.

FIG. 1 shows the first embodiment obtained by applying the present invention to a simple matrix drive type liquid crystal display device. A liquid crystal display device A' shown in FIG. 1 is formed such that a pair of transparent rectangular substrates 20 and 21 are integrated with each other to interpose a sealing material 22 therebetween.

In the configuration shown in FIG. 1, the substrate 20 is generally called an upper substrate, and the substrate 21 is generally called a lower substrate. As shown in FIG. 1, when the substrates 20 and 21 are made laterally upright such that the substrates 21 and 20 are arranged on the front and rear sides, respectively, the substrate 20 is taller than the substrate 21, and the substrate 21 has a lateral width larger than that of the substrate 20. The substrate 20 and the substrate 21 are integrated with each other such that the bottom-side portion and the right-side portion are adjusted to each other, and a portion of the substrate 20 upwardly sticking out of the substrate 21 is defined as a projection end portion 23, and a portion of the substrate 21 sticking out of the substrate 20 on the left-side portion side is defined as a projection end portion 24.

The sealing material 22 consisting of a resin is interposed between the substrate 20 and 21 such that the

sealing material 22 is sandwiched by the substrates 20 and 21 along the corners of the overlapping portions of the substrates 20 and 21. The sealing material 22 is constituted by an annular portion 22a arranged in the form of an almost rectangularly annular shape along the peripheral portions of the overlapping portions of the substrates 20 and 21, extension portions 22b which are almost parallel drawn while the extension portions 22b are spaced apart from each other on the central portions of the substrates 20 and 21 on the right side toward the right sides of the substrates 20 and 21 to have a liquid crystal injection portion 26 formed on the right side of the substrates 20 and 21, and a sealed portion 22c formed by stopping up the injection portion 26. On the slightly inner side of the injection portion 26, a linear bank member 27 consisting of a resin having a length almost equal to the width of the injection portion 26 is arranged almost parallel to the right side of the substrate 20 while the bank member 27 is sandwiched by the substrates 20 and 21.

A large number of stripe-shaped display electrodes are parallel formed on the opposite surfaces of the substrates 20 and 21 inside the sealing material 22, and the large number of display electrodes formed on the substrate 20 and the large number of display electrodes formed on the substrate 21 are opposite to each other at angles of 90° and

arranged in the form of a matrix. A rectangular electrode forming region 30 which is slightly smaller in area than the area of the annular sealing material 22 is formed inside the sealing material 22.

On the surface of the projection end portion 23 of the substrate 20 on the substrate 21 side, drawn electrodes 23a drawn from the large number of display electrodes are formed in an array. On the surface of the projection end portion 24 of the substrate 21 on the substrate 20 side, drawn electrodes 24a drawn from the large number of display electrodes are also formed in an array. These drawn electrodes 23a and 24a are used to attach a drive IC or the like of the liquid crystal display device thereto.

More specifically, in addition to the electrode layers, overcoat layers and alignment films are stacked on the opposite surface sides of the substrates 20 and 21, a color filter is further arranged when a color display is performed.

However, in the description of this embodiment, descriptions of these parts are omitted.

On the almost entire surface of the substrate 21 (lower substrate) on the outer side, a metal reflective film 31 consisting of deposited Al or the like. In the metal reflective film 31, an unformed region 31a of the metal reflective film is formed on a portion corresponding to the liquid crystal injection portion 26, and an unformed portion

31b of a metal reflective film is formed on a portion corresponding to the drawn electrode forming region of the substrate 21.

The unformed region 31a of the metal reflective film has a shape obtained by forming a rectangular notched portion in the metal reflective film 31. The longitudinal width of the unformed region 31a (length parallel to the short side of the substrate 21 in FIG. 1) is made larger than the longitudinal width of the liquid crystal injection portion 26 and smaller than the longitudinal width of the substrate 20. The unformed region 31a is formed to have such a lateral width (length parallel to the long side of the substrate 21 in FIG. 1) that the unformed region 31a extends from the right side end (exit portion of the injection portion 26) of the substrates 20 and 21 to a position between the bank member 27 and the electrode forming region 30.

On the other hand, the unformed portion 31b of the metal reflective film has a shape obtained by forming a rectangular notched portion in the metal reflective film 31.

The longitudinal width of the unformed portion 31b (length parallel to the short side of the substrate 21 in FIG. 1) is made slightly larger than that of the forming region of the drawn electrodes 24a and equal to or smaller than the short side of the substrate 21. The unformed region 31a is formed

If the liquid crystal display device A' having the structure shown in FIG. 1 is used, the structure is preferable in the following case. In the processes of manufacturing the liquid crystal display device A', the substrates 20 and 21 are adhered to each other through the sealing material 22, and an operation of injecting a liquid crystal from the liquid crystal injection portion 26 into a space surrounded by the substrates 20 and 21 and the sealing material 22 is performed, and the injection portion 26 is sealed with a resin.

More specifically, as in the conventional case described with reference to FIG. 10, pairs of substrates 20 and 21 are vertically arranged in an array, and a resin is sequentially injected into the liquid crystal injection portions 26 of the substrates 20 and 21 to form the sealed portions 22c, and the injection portions 26 are closed. In this case, the positions of the injection portions 26 can be easily checked from the outside because the unformed regions 31a of the metal reflective films exist around the injection portions 26. Therefore, in either one of a case in which

the plurality of injection portions 26 are visually checked and a case in which the plurality of injection portions 26 are checked by an imaging device such as a television camera, it can be easily checked whether the injection portions 26 can be reliably stopped up by the resin sealed portions 22c from the outside of the arrayed substrates 1 and 2.

Since the bank member 27 is formed inside the liquid crystal injection portion 26, the injected resin is retained by the bank member 27, reliably spreads on the inside of the injection portion 26, and is filled in the injection portion 26. For this reason, if the filling state is checked, it can be easily determined whether the injection portion 26 is completely sealed. The filling state of the injected resin can also be easily checked by a visual check or the like from the outside or by an image analyzer or the like because of the unformed region 31a.

Since the unformed portion 31b of the metal reflective film formed on the end side of the substrate 21 conceals the drawn electrodes 24a of the display electrodes, when a drive IC or the like is connected to the drawn electrodes 24a, the connection portions between the IC and the drawn electrodes 24a are not concealed from the rear surface side of the substrate 21.

In addition, although defective liquid crystal injection may occur in the process of injecting a liquid

crystal, before the injection portion 26 of the substrates 20 and 21 having the defective liquid crystal injection is sealed, the injection portion 26 can be easily checked by a visual check or an image analyzer through the unformed region 31a. For this reason, a sealing operation is not performed to the substrates 20 and 21, and the substrates 20 and 21 can be sealed after a liquid crystal injection operation is performed again. Therefore, the substrates 20 and 21 in which defective liquid crystal injection occurs can be prevented from being sealed, and a defective product can be prevented from being manufactured.

In order to form the metal reflective film 31 having the configuration described above on the rear surface side of the substrate 21, for example, resists are formed on portions corresponding to the unformed region 31a of the metal reflective film and the unformed portion 31b of the metal reflective film on the substrate 21, and Al is deposited. After an Al deposition film is formed, the resists are peeled and removed. In this manner, the metal reflective film 31, the unformed region 31a, and the unformed portion 31b can be formed at desired positions of the substrate 21.

FIG. 2 shows the second embodiment obtained by applying the present invention to a simple matrix drive type liquid crystal display device. The same reference numerals as in

The liquid crystal display device B' shown in FIG. 2 has a metal reflective film having a shape different from that in the liquid crystal display device A' shown in FIG. 1.

A metal reflective film 41 in this embodiment is formed on the rear surface side of the substrate 21 as in the previous embodiment, in the metal reflective film 41 on the liquid crystal injection portion 26 side, in addition to the same region as the unformed region 31a of the previous embodiment, an unformed region 41a of the metal reflective film which occupies a region extending a position near the annular portion 22a of the sealing material 22 to the right end of the substrate 21 is formed. An unformed portion 41b of the metal reflective film corresponding to the almost entire area of the projection end portion 24 of the substrate 21 is formed on the left end side of the substrate 21. In this embodiment, the metal reflective film 41 is formed to cover a display electrode forming region 40 and the annular portion 22a of the sealing material formed around the display electrode forming region 40. However, in FIG. 2, both the peripheral portions of the metal reflective film 41 on the bottom side and the upper side of the substrate 21 are formed up to a slightly inside position of the outer

wider than that of the structure of the first embodiment.

FIG. 3 is used to explain a forming position of a metal reflective film. In either one of the liquid crystal display device A' of the first embodiment described above and the liquid crystal display device B' of the second embodiment, the metal reflective film 31 or the metal reflective film 41 is formed on the rear surface side of the substrate 21. However, such a structure has a sectional structure as shown in FIG. 3A.

In contrast to this, as a structure in which a metal reflective film is formed on the surface of the substrate 21 on the liquid crystal side as shown in FIG. 3B, the metal reflective film 51 is formed to have one of the planar shapes shown in FIG. 1 and FIG. 2, so that a liquid crystal display device C can also be constituted.

The liquid crystal display device C according to the third embodiment having the above structure is structured such that the metal reflective film 51 is incorporated in the substrate. For this reason, when electrodes, an overcoat layer, a color filter layer, and the like are formed on the metal reflective film 51 incorporated in the substrate 21 described above, the liquid crystal display device C shown in FIG. 3B can be constituted.

In the structure shown in FIG. 3A, respective layers such as electrode layers, color filter layers, and alignment

layers stacked on the opposite surface sides of the substrates 20 and 21 are omitted. In the structure shown in FIG. 3B, respectively layers such as electrode layers, color filter layers, and alignment layers stacked on the metal reflective film 51 and the opposite surface side of the substrate 20 are omitted.

FIG. 4 to FIG. 6 show the fourth embodiment obtained by applying the present invention to a simple matrix drive type liquid crystal display device. The same reference numerals as in the liquid crystal display device A' shown in FIG. 1 denote the same components in a liquid crystal display device D shown in FIG. 4 to FIG. 6, and a description thereof will be omitted.

The liquid crystal display device D of this embodiment has one characteristic feature described below. That is, drawn terminals 23a' connected to display electrodes formed on the substrate 20 are formed on the projection end portion 24 of the substrate 21, not formed on the projection end portion 23 side of the substrate 20. In this case, first drawn electrodes (drawn terminals) 24a' for the display electrodes of the substrate 21 are formed in an array on the projection end portion 24 of the substrate 21. However, on an end side of the low on which the first drawn electrodes 24a' are formed, for example, on the side near the projection end portion 23 of the substrate 20 on the

projection end portion 24 of the substrate 21, the plurality of second drawn terminals 23a' (drawn terminals) are formed in an array.

On the right end side of a metal reflective film 61 formed on the rear surface side of the substrate 21 of this embodiment, an unformed region 61a having the same shape as that of the unformed region 41a of the second embodiment described above is formed. The unformed region 61a is formed such that, due to the existence of the unformed region 61a, the liquid crystal injection portion 26 and a portion therearound can be seen from the rear surface side of the substrate 21, and the entire area of the right end side of the substrate 21 can be easily visually checked from the rear surface side of the substrate 21. On the left end side of the metal reflective film 61, an unformed portion 61b corresponding to an almost entire area of the projection end portion 24 of the substrate 21 and also corresponding to the portion inside the forming region of the second drawn terminals 23a' is formed. The unformed portion 61b is formed such that the entire area of the projection end portion 24 and the inside portion of the second drawn terminals 23a' can be easily visually checked from the rear surface side of the substrate 21. The inside portion of the second drawn terminals 23a' of means a portion around the annular portion 22a of the sealing material 22 located

09334387-064659

inside the second drawn terminals 23a'. An extension portion 61c of the unformed portion 61b is formed to correspond to the inside portion.

The structure of connection portions between the display electrodes of the substrate 20 and the second drawn terminals 23a' will be described below on the basis of a liquid crystal display device D', in which the metal reflective film 61 is incorporated, according to the embodiment shown in FIG. 5A.

In the structure of this embodiment, as shown in FIG. 5A, an insulating layer 65, a resin layer 66, and a resin layer 67 are stacked on the substrate 21, and the metal reflective film 61 is incorporated in a portion corresponding to a display region on the center portion side of the resin layer 67, and color filters 68 are formed in the display region of the resin layer 67. A flat film 69 which consists of a resin and covers the color filters 68 and the resin layer 67 is formed, stripe-shaped electrodes 70 are formed on the flat film 69 on the color filters 68, and an alignment film 71 is formed to cover the stripe-shaped electrodes 70 in the display region. An insulating layer 73 is formed on the lower surface side of the substrate 20, stripe-shaped electrodes 74 are formed on the lower surface side of the insulating layer 73 in a direction vertical to the electrodes 70 on the substrate 21

The stripe-shaped electrodes 74 are formed such that the ends of the stripe-shaped electrodes 74 are extended to reach the sealing material 22, and a large number of drawn terminals 23a' are formed on the flat film 69 on the substrate 21 side such that the drawn electrodes 23a' direct from the position of the sealing material 22 toward the outside and extends to the outside parallel to the electrodes 74 on the substrate 20 side. A large number of conductive particles 75 are diffused into the sealing material 22, and the electrodes 74 are connected to the drawn terminals 23a' through the conductive particles 75.

When a proper number of conductive particles 75 constituting the sealing material 22 and having appropriate particle sizes are diffused into the region constituting the sealing material 22, as shown in FIG. 5A or FIG. 6A, the electrodes 74 are electrically connected to the drawn terminals 23a' in the thickness direction of the sealing material 22, and adjacent electrodes 74 are prevented from being short-circuited in the surface direction.

As the conductive particles 75 in the above configuration, particles obtained by forming conductive films consisting of Au or Cu on the outer surfaces of resin micro balls can be used. When resin micro balls cannot be

When the connection structure described on the basis of FIG. 5A and FIG. 6A is employed, the structure of the liquid crystal display device D having the structure shown in FIG. 4 can be realized. When the structure of this embodiment is used, the drawn electrodes 23a' and 24a' can be arranged on only the end side of the substrate 21. For this reason, a drive IC or the like is to be connected, a connection operation may be performed to only one substrate 21. Therefore, an operation of attaching a drive IC in this structure is easier than that in a structure in which a drive IC must be attached to both the substrates 20 and 21.

In this embodiment, the electrodes 74 on the substrate 20 side and the drawn terminals 23a' on the substrate 21 side are connected to each other by the conductive particles

reach the resin layer 66, a problem such as a short circuit is not posed. In contrast to this, if a structure in which the unformed region 61c is formed in the metal reflective film 61 is used, electrodes may be short-circuited.

When the conductive particles 75 reach the metal reflective film 61 in the structure in which the unformed region 61c is not formed as shown in FIG. 6B, the metal reflective film 61 is short-circuited to the drawn terminals 23a'. The structure is not preferable. When the unformed region 61c is formed in the metal reflective film 61 as described above, the metal reflective film 61 and the drawn terminals 23a' can be advantageously prevented from being short-circuited to each other.

Example

As conductive particles, micropearls (tradename: Micropearl Au available from Sekisui Fine Chemical Co., Ltd.) obtained by performing conductive plating to plastic particles were applied.

A mixture of 100 weight parts of sealing resin (thermosetting epoxy resin), 1.5 weight parts of glass fiber spacer (6.5 $\mu\text{m}\phi$), and 2 weight parts of Au-plated micropearl (tradename: XN-5A6.75 $\mu\text{m}\phi$ available from Mitsui Toatsu Chemicals, Inc.) was used as a sealing resin to constitute a sealing material. In-cell-diffusion micropearls (6.38 $\mu\text{m}\phi$) diffused between the substrates 20 and 21 to uniform

intervals between the substrates 20 and 21 were used at a rate of 120 particles/mm², and a liquid crystal display device having the sectional structure shown in FIGS. 5A and 5B was assembled. As a result, the concentration of the Au-plated micropearl in the sealing material could be made 400±150 particles/mm².

In the substrate connection structure of the liquid crystal display device using the sealing material having the concentration and the structure described above, of electrodes formed on a pair of substrates, each having a drawn electrode with of 40 μm, arranged at drawn electrode intervals of 30 μm, adjacent electrodes in the substrate surface direction were not short circuits, and the electrodes of both the substrates which were opposite to each other in the thickness direction of the sealing material could be electrically connected to each other through the sealing material.

As the metal reflective film, an Al diffusion film formed on the rear surface side of the substrate was used. The unformed region and the unformed portion of the Al deposition film could be obtained by the following manner. That is, resists were formed on positions corresponding to the unformed region and the unformed portion on the substrate, Al was deposited, and the resists were peeled and removed after an Al deposition film was formed.

As has been described above, according to the present invention, since the unformed region of the metal reflective film is formed on a portion including the injection portion of the sealing material outside the display electrode forming region, the position of the liquid crystal injection portion can be easily checked from the outside through the metal reflective film. Therefore, after a liquid crystal is injected from the injection portion of the sealing material into a portion between substrates, when operations of uprightly arraying a large number of substrates, sequentially injecting a resin into a large number of injection portions, and stopping up the injection portions are performed, the positions of the injection portions can be seen without being disturbed by the metal reflective films of other adjacent substrates.

Therefore, since the positions of the injection portions obtained by resin injection can be correctly checked, the operation of stopping up the injection portions

can be easily and reliably performed. Since the resin filled in the injection portions can be easily checked from the outside of the substrates through the metal reflective films of the plurality of substrates, it can be easily checked by a visual check or an imaging analyzer such as a television camera whether the liquid crystal injection portions of the sealing materials can be completely sealed with resin, and defectiveness such as leakage of a liquid crystal in the liquid crystal sealing process can be prevented.

Even if uneven injection or the like occurs in the liquid crystal injection process to cause defectiveness, the uneven liquid crystal injection can be easily checked before the injection portion is sealed with resin. Resin sealing is stopped, liquid crystal injection is performed again, and the injection portion can be sealed. For this reason, probability that the substrates in which uneven injection occurs are sealed with resin can be reduced. Defectiveness can be prevented from occurring, and an advantage that a yield is increased can be obtained.

In addition, according to the present invention, drawn electrodes for display electrodes are formed on one side edge outside the display electrode forming region of one substrate, and the unformed portion of the metal reflective film is formed in the drawn electrode forming region. For

09344337-064699

this reason, drawn electrode can be easily formed without being disturbed by the metal reflective film, and the terminals of a drive IC or the like can be easily and reliably connected.

According to the present invention, since second drawn electrodes of one substrate and display electrodes of the other substrate are connected to each other through an electrode connection means of a sealing material, metal reflective films do not exist on the connection portions, and the connection portions can be easily formed. When a drive IC or the like is joined to the drawn electrodes, the connection portions can be easily checked without being disturbed by the metal reflective film.

Outside the display electrode forming region on one substrate of the structure described above, an unformed region of the metal reflective film may be formed on a portion including an injection portion of a sealing material.

Since the unformed region of the reflective film is formed on the portion including the injection portion of the sealing material, the position of the injection portion can be easily checked. Therefore, when operations of uprightly arraying a large number of substrates, sequentially injecting a resin into a large number of injection portions, and stopping up the injection portions are performed, the positions of the injection portions can be easily seen

Of conductive particles of the sealing material, conductive particles sandwiched by the electrodes of a pair of opposite substrates, i.e., conductive particles existing in the thickness direction of the substrates or the sealing material are sandwiched by the electrodes of a pair of substrates to be in contact with these electrodes, thereby electrically connecting the electrodes to each other.

However, since conductive particles existing in the surface direction of the substrates are spaced apart from each other, the electrodes adjacent to each other in the substrate surface direction are not short-circuited.

Therefore, the electrodes of the substrates which are opposite to each other in the thickness direction of the sealing material without short-circuiting the electrodes which are adjacent to each other in the surface direction of the substrates.

In addition, when a structure in which an unformed region of a metal reflective film is formed is used, if conductive particles press and break through drawn electrodes and other films on the substrate to reach the inside of the structure, any problem that the metal reflective film and the drawn electrodes are short-circuited to each other is not posed because the metal reflective film does not exist on the portion where the conductive particles reach.

664490/34446660

WHAT IS CLAIMED IS:

1. A liquid crystal display device comprising one substrate on which a metal reflective film is formed, the other substrate arranged opposite to the substrate, a sealing material, interposed between the pair of substrates, for surrounding, together with the substrates, a liquid crystal injection space formed between the substrates, and a liquid crystal sealed into the liquid crystal injection space, wherein

a liquid crystal injection portion is formed on the sealing material, a plurality of display electrodes are formed on a substrate surface in a region in which the liquid crystal is sealed, and

on one of the substrates, outside the display electrode forming region, an unformed region of the metal reflective film is formed on a portion including the injection portion of the sealing material.

2. A liquid crystal display device wherein, on one substrate, on which a metal reflective film is formed, of a pair of substrates which hold a liquid crystal therebetween, drawn electrodes of the display electrodes are formed at the edges of the substrates outside a region in which a plurality of display electrodes are formed on substrate

0034337.064600

an unformed portion of the metal reflective film is formed in a region in which the second drawn electrode and the display electrode of the other of the substrates are connected to each other on the sealing material.

4. A liquid crystal display device according to claim 3, wherein, on one of the substrates, outside the display electrode forming region, an unformed region of the metal reflective film is formed on a portion including the injection portion of the sealing material.

5. A liquid crystal display device according to claim 3, wherein, on one of the substrates, outside the display element forming region, unformed portions of the metal reflective films are formed in the first drawn electrode forming region and the second drawn electrode forming region.

6. A liquid crystal display device according to claim 3, wherein the electrode connection means arranged on the sealing material consists of conductive particles added to the region constituting the sealing material.

009490-CE4EE60

ABSTRACT OF THE DISCLOSURE

The present invention has an object to provide a liquid crystal display device which, when a liquid crystal injection portion is sealed and stopped up with a resin, makes it possible to precisely and easily perform the operation and makes it possible to detect defective liquid crystal injection. The liquid crystal display device comprises one substrate on which a metal reflective film is formed, the other substrate arranged opposite to the substrate, a sealing material, interposed between the pair of substrates, for surrounding, together with the substrates, a liquid crystal injection space formed between the substrates, and a liquid crystal sealed into the liquid crystal injection space, and is characterized in that a liquid crystal injection portion is formed on the sealing material, a plurality of display electrodes are formed on a substrate surface in a region in which the liquid crystal is sealed, and, on one of the substrates, outside the display electrode forming region, an unformed portion of the metal reflective film is formed on a portion including the injection portion of the injection material.

00334387-064699

FIG. 1




FIG. 3A




FIG. 3B




FIG. 5B




FIG. 6A




FIG. 6B




FIG. 7
PRIOR ART




FIG. 8
PRIOR ART






FIG. 9
PRIOR ART



669490-2844E60

FIG. 10
PRIOR ART



09344387.061699

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Declaration and Power of Attorney For Patent Application

特許出願宣言書及び委任状

Japanese Language Declaration

日本語宣言書

下記の氏名の発明者として、私は以下の通り宣言します。 As a below named inventor, I hereby declare that:

私の住所、私書箱、国籍は下記の私の氏名の後に記載された通りです。

My residence, post office address and citizenship are as stated next to my name.

下記の名称の発明に関して請求範囲に記載され、特許出願している発明内容について、私が最初かつ唯一の発明者（下記の氏名が一つの場合）もしくは最初かつ共同発明者であると（下記の名称が複数の場合）信じています。

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled

Liquid Crystal Display Device

上記発明の明細書（下記の欄でx印がついていない場合は、本書に添付）は、

the specification of which is attached hereto unless the following box is checked:

☐ 月 日に提出され、米国出願番号または特許協定条約国際出願番号を _____ とし、
(該当する場合) _____ に訂正されました。☐ was filed on _____
as United States Application Number or
PCT International Application Number
_____ and was amended on
_____ (if applicable).

私は、特許請求範囲を含む上記訂正後の明細書を検討し、内容を理解していることをここに表明します。

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

私は、連邦規則法典第37編第1条56項に定義されるとおり、特許資格の有無について重要な情報を開示する義務があることを認めます。

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Japanese Language Declaration

(日本語宣言書)

私は、米国法典第35編119条(a)-(d)項又は365条(b)項に基づき下記の、米国外の国の少なくとも一カ国を指定している特許協力条約365(a)項に基づく国際出願、又は外国での特許出願もしくは発明者証の出願についての外国優先権をここに主張するとともに、優先権を主張している、本出願の前に出願された特許または発明者証の外国出願を以下に、枠内をマークすることで、示しています。

Prior Foreign Application(s)

外国での先行出願

10-170373

(Number)

(番号)

Japan

(Country)

(国名)

17/06/1998

(Day/Month/Year Filed)

(出願年月日)

Priority Not Claimed

優先権主張なし

☐

(Number)

(番号)

(Country)

(国名)

(Day/Month/Year Filed)

(出願年月日)

☐

私は、第35編米国法典119条(e)項に基づいて下記の米国外特許出願規定に記載された権利をここに主張いたします。

(Application No.)

(出願番号)

(Filing Date)

(出願日)

(Application No.)

(出願番号)

(Filing Date)

(出願日)

私は、下記の米国法典第35編120条に基づいて下記の米国外特許出願に記載された権利、又は米国を指定している特許協力条約365条(c)項に基づく権利をここに主張します。また、本出願の各請求範囲の内容が米国法典第35編112条第1項又は特許協力条約で規定された方法で先行する米国外特許出願に開示されていない限り、その先行米国外出願書提出日以降で本出願書の日本国内または特許協力条約国際提出日までの期間中に入手された、連邦規則法典第37編1条56項で定義された特許資格の有無に関する重要な情報について開示義務があることを認識しています。

(Application No.)

(出願番号)

(Filing Date)

(出願日)

(Status: Patented, Pending, Abandoned)

(現況: 特許許可済、係属中、放棄済)

(Application No.)

(出願番号)

(Filing Date)

(出願日)

(Status: Patented, Pending, Abandoned)

(現況: 特許許可済、係属中、放棄済)

私は、私自身の知識に基づいて本宣言書中で私が行なう表明が真実であり、かつ私の入手した情報と私の信じることに基づく表明が全て真実であると信じていること、さらに故意になされた虚偽の表明及びそれと同等の行為は米国法典第18編第1001条に基づき、罰金または拘禁、もしくはその両方により処罰されること、そしてそのような故意による虚偽の表明を行なえば、出願した、又は既に許可された特許の有効性が失われることを認識し、よってここに上記のごとく宣誓を致します。

I hereby claim foreign priority under Title 35, United States Code, Section 119 (a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

I hereby claim the benefit under Title 35, United States Code, Section 119(e) of any United States provisional application(s) listed below.

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States application(s), or 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code Section 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Section 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of application.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

0651-0032-0644-60

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Japanese Language Declaration
(日本語宣言書)

委任状： 私は下記の発明者として、本出願に関する一切の手続きを米特許商標局に対して遂行する弁理士または代理人として、下記の者を指名いたします。(弁護士、または代理人の氏名及び登録番号を明記のこと)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith (list name and registration number)

See Attachment A

書類送付先

Send Correspondence to:

Brinks Hofer Gilson & Lione
P.O. Box 10395
Chicago, Illinois 60610
(312) 321-4200

直接電話連絡先： (名前及び電話番号)

Direct Telephone Calls to: (name and telephone number)

唯一または第一発明者名	Full name of sole or first inventor	Takashi Date
発明者の署名	Inventor's signature	Takashi Date
日付	Date	May 31, 1999
住所	Residence	Fukushima-ken, Japan
国籍	Citizenship	Japan
私書箱	Post Office Address	c/o ALPS ELECTRIC CO., LTD. 1-7 Yukigaya, Otsuka-cho, Ota-ku, Tokyo, Japan
第二共同発明者	Full name of second joint inventor, if any	Toshiaki Hoshino
第二共同発明者	Second inventor's signature	Toshiaki Hoshino
日付	Date	May 31, 1999
住所	Residence	Fukushima-ken, Japan
国籍	Citizenship	Japan
私書箱	Post Office Address	c/o ALPS ELECTRIC CO., LTD. 1-7 Yukigaya, Otsuka-cho, Ota-ku, Tokyo, Japan

(第三以降の共同発明者についても同様に記載し、署名をすること)

(Supply similar information and signature for third and subsequent joint inventors.)

